

**Smaller, lighter and  
even more powerful**

**PREBENA**®

www.prebena.com

## **Pneumatic Stapler 4C-L50** for staples type L from 19 - 50 mm (3/4" - 2")



**easy clear catch**

**single and bump fire**

**multifunction impact**

**Smooth impact:**  
Fermacell, plasterboard, boxes, corrugated cardboards, cedar and shake shingles, chipboards, packaging, substructures, saving formwork, cardboard pallets, prefab construction and much more.

**Splined impact:**  
groove and tongue profile, watherboarding, wire fences, windbreak fences and much more.

**Technical details:**  
Weight: 2,2 kg (4.85 lb.)  
Operating pressure:  
approx. 5 - 8 bar (71 - 114 psi.)  
Air requirement:  
approx. 1,72 l / staple (0.378 gal./ staple)

**Tested according to**  
**DIN 1052:2008-12**

**Type L**  
from  
19 - 50 mm  
(3/4" - 2")  
Wire size:  
1.4x 1.65 mm  
(0.055x0.055 in.)  
Crown:  
10,7 mm  
(0.421 in.)

**recommended by:**  
**xella** Neues Bauen  
**fermacell**

**ETA** **CE**  
European Technical Assessment  
for staples as wood connecting fasteners  
ETA-16/0101

**180°**

- 180° rotatable for work with smooth ore splined imact
- adjustable depth control
- available with and without impact

### **Standard equitment:**

- increased driver
- adjustable exhaust
- ergonomic handle
- safety device

**PREBENA Wilfried Bornemann GmbH & Co. KG**

Seestraße 20 - 26 • 63679 Schotten - Germany

Phone: +49 (0) 6044/9601-0 • Fax: +49 (0) 6044/9601-820 • info@prebena.com