

Fast stapling in industrial manufacturing

PREBENA®

www.prebena.com

Pneumatic-Industrial Stapler MODUL WP-130 for staples type WP from 75 - 130 mm (3"-5-1/8")

Vertical pneumatic connection

Industrial packaging for quick reloading

Changeable magazine for easy and quick loading

Empty shot safety device

Staple dimensions:
26,7 mm
1,8 x 2,08 mm
75
85
100
110
120
130

EUROCODE 5
CE EN 14592

Technical details:
Weight: 15,5 kg (34.17 lb.)
Weight incl. staples: 19,75 kg (43.54 lb.)
Operating pressure: 5 - 7,5 bar (72-107 psi.)
Air requirement: 5,1 l/staple up to 6 bar
(1.35 gal./staple at 87.02 psi.)
Magazine capacity:
15 staple bars = 780 staples
Measurements: LxBxH: 500 x 141 x 531 mm
(LxWxH: 19.69 x 5.55 x 20.91 in.)

- Cooling of the bumper by equipment air
→ longer service intervals
- Large volume of air inside the body
→ Fast rate of shooting
- Max. rate of fire
→ 12 shots / second

- Triggering system:
External triggering by PCL program
- Magazine system:
Top load by changing magazine
- Control port:
XLR-port 6-pole
- Ready for installation

PREBENA Wilfried Bornemann GmbH & Co. KG

Seestraße 20-26 • D-63679 Schotten • Tel.: 06044/9601-0 • Fax: 06044/9601-820 • info@prebena.de